

GRADIENT ANALYSIS OF CARBON MONOXIDE AND
METHANE IN POLLUTED AND OTHER
NEARSHORE HABITATS

James Taylor Welch

Gradient Analysis of Carbon Monoxide
and Methane in Polluted and Other
Nearshore Habitats

by

James Taylor Welch
Lieutenant, United States Navy
B.S.Chem., Purdue University, 1966

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN OCEANOGRAPHY

from the

NAVAL POSTGRADUATE SCHOOL
March 1973

ABSTRACT

A system for the determination of dissolved gases in seawater by gas chromatography was constructed and used to find the concentrations of methane and carbon monoxide in a variety of habitats around the Monterey Peninsula. Methane was shown to have a maximum of 2.8×10^{-4} ml/l at 50 meters at the open ocean station, with a surface value of 1.1×10^{-4} ml/l. The surface waters at the nearshore stations were almost three times this value. Methane was also shown to be an effective tracer for sewage effluent. The carbon monoxide maximum of 2.1×10^{-4} ml/l was found at 15 meters which correlated closely with primary productivity (Rowney 1973). The surface value of 0.81×10^{-4} ml/l was lower than the nearshore values. All stations sampled were found to be highly supersaturated with both gases. This indicates that in this area, the ocean is a major source of both methane and carbon monoxide.

TABLE OF CONTENTS

I.	INTRODUCTION -----	9
II.	EQUIPMENT -----	10
A.	GAS TRAPPING SYSTEM -----	10
1.	Sample Transfer -----	10
2.	Stripping Chamber -----	10
3.	Trapping Columns -----	12
4.	Backflush Lines -----	12
B.	CALIBRATION SYSTEM -----	13
C.	GAS CHROMATOGRAPH -----	13
1.	Modifications -----	13
D.	CATALYST FURNACE -----	15
E.	RECORDER -----	15
III.	EXPERIMENTAL METHODS -----	16
A.	SAMPLE COLLECTION -----	16
B.	SAMPLE ANALYSIS -----	19
IV.	RESULTS -----	24
A.	OPEN OCEAN DEEP STATION -----	24
1.	Methane -----	24
2.	Carbon Monoxide -----	24
3.	Primary Productivity -----	24
B.	TEMPORAL STUDIES -----	24
C.	GRADIENT ANALYSIS -----	30
D.	TRANSECTS-----	42
V.	DISCUSSION OF RESULTS -----	50
A.	PRECISION AND ACCURACY -----	50

B.	OPEN OCEAN DEEP STATION -----	50
C.	TEMPORAL STUDY -----	51
D.	GRADIENT ANALYSIS -----	54
E.	TRANSECTS -----	55
VI.	SUMMARY -----	57
VII.	RECOMMENDATIONS -----	58
	APPENDIX A -----	59
	APPENDIX B -----	61
	APPENDIX C -----	62
	APPENDIX D -----	63
	BIBLIOGRAPHY -----	80
	INITIAL DISTRIBUTION LIST -----	82
	FORM DD 1473 -----	83

LIST OF TABLES

<u>TABLE NO.</u>		<u>PAGE NO.</u>
1.	Seawater Sampling Stations -----	18
2.	Methane Concentrations in Monterey Canyon -----	26
3.	Carbon Monoxide Concentrations in Monterey Canyon -----	28
4.	Methane and Carbon Monoxide Concentrations at Del Monte Beach -----	32
5.	Methane and Carbon Monoxide Concentrations at Point Cabrillo -----	34
6.	Methane and Carbon Monoxide Concentrations at Point Pinos North -----	36
7.	Methane and Carbon Monoxide Concentrations at Point Pinos South -----	38
8.	Methane and Carbon Monoxide Concentrations at Point Joe -----	40
9.	Methane and Carbon Monoxide Concentrations for the Transect Along Del Monte Beach -----	45
10.	Methane and Carbon Monoxide Concentrations for the Transect from Del Monte Beach to the R-4 Buoy -----	47
11.	Methane and Carbon Monoxide Concentrations for the Transect from Point Cabrillo to the R-4 Buoy -----	49

LIST OF FIGURES

<u>Figure No.</u>		<u>Page No.</u>
1.	Schematic diagram of the dissolved gas analysis system --	11
2.	Detailed schematic diagram of the calibration system and traps -----	14
3.	Chart showing location of nearshore stations -----	17
4.	Chromatogram from a sample run -----	21
5.	Chromatogram from a calibration run -----	23
6.	Vertical distribution of CH ₄ at the Deep Ocean Station in Monterey Canyon -----	25
7.	Vertical distribution of CO at the Deep Ocean Station in Monterey Canyon -----	27
8.	Vertical distribution of Primary Productivity in the upper 50 meters of the Deep Ocean Station in Monterey Canyon -----	29
9.	CH ₄ and CO concentrations in the surface waters at Del Monte Beach -----	31
10.	CH ₄ and CO concentrations in the surface waters at Point Cabrillo -----	33
11.	CH ₄ and CO concentrations in the surface waters at Point Pinos North -----	35
12.	CH ₄ and CO concentrations in the surface waters at Point Pinos South -----	37
13.	CH ₄ and CO concentrations in the surface waters at Point Joe -----	39
14.	Surface temperature -----	41
15.	CH ₄ and CO gradients between the five nearshore stations-	43
16.	CH ₄ and CO concentrations for a transect along Del Monte Beach -----	44
17.	CH ₄ and CO concentrations for transects from Del Monte Beach to the R-4 Bell Buoy -----	46

18. CH_4 and CO concentrations for a transect from Point
Cabrillo to the R-4 Bell Buoy ----- 48
19. Plot of CH_4 versus CO in the Deep Ocean Station in
the Monterey Canyon. Numbers indicate depth in meters -- 52

ACKNOWLEDGEMENTS

The author wishes to express his appreciation to:

Dr. Eugene D. Traganza, for his guidance and inspiration in all phases of this project, and his close attention to detail in the preparation of this thesis.

Dr. Charles F. Rowell, for his advice, assistance and critical review of this work.

Dr. Eugene C. Haderlie for his critical review of the manuscript.

Dr. John W. Swinnerton and Mr. Robert A. Lamontagne of the Naval Research Laboratory for their technical advice and support throughout this project.

Mr. Kenneth J. Graham, Department of Research Administration, Robert Sanders of the Department of Physics and Chemistry, Roy Edwards of the Department of Mechanical Engineering, and Bill Penpraze of the Department of Electrical Engineering, for their help in the construction and trouble-shooting of the system.

The Naval Postgraduate School boat crew and Lt. John V. Rowney for their enthusiastic assistance in sample collection under often adverse weather conditions.

A special thanks to Mr. Robert Scheile of the Research Department for his expert technical assistance in the design and construction of the system.

I. INTRODUCTION

The ocean has been shown to be supersaturated with carbon monoxide (Swinerton, Linnenbom, and Lamontagne, 1970). The sources for this gas may be plants (Chapman and Tocher, 1966; Delwiche, 1970; Loewus and Delwiche, 1963), animals (Pickwell and Barham, 1964; Pickwell, 1970; Barham, 1963; Wittenberg, 1960), and microorganisms (Junge, et. al., 1971). These results led to the hypothesis that carbon monoxide production might be related to primary productivity. The highly productive waters of Monterey Bay were thought to be an excellent location to test this hypothesis.

Methane has also been reported as being present in surface waters (Swinerton, Linnenbom, and Cheek, 1969). Since this gas is a product of anaerobic decomposition of organic matter it was felt that it might be useful as a pollution tracer from sewage outfalls. Again, Monterey Bay provides an excellent environment for these studies.

In order to measure these gases, the highly sensitive methods of gas chromatography were used. The gas chromatograph has long been one of the analytical chemist's most useful instruments. It was not until 1962 that a practical system for oceanographic analyses was developed (Swinerton, Linnenbom, and Cheek, 1962). Today, the shipboard determination of dissolved gases by gas chromatography is one of the most valuable methods available to the chemical oceanographer.

II. EQUIPMENT

The system used was essentially that described by Swinnerton, Linenbom, and Cheek (1968). A calibration system was added and minor modifications were made in the sample transfer system. The entire system is shown in Figure 1.

A. GAS TRAPPING SYSTEM

The separation is accomplished in four major steps. They are sample transfer, stripping, trapping, and backflushing.

1. Sample Transfer

A helium line is connected to the side port of a Swagelok heat exchanger "T". A standard taper joint is attached to the bottom of this "T" that fits into the filled sample bottle. A 1/8" stainless steel tube runs from the bottom of the sample bottle through the heat exchanger "T" and is connected to the bottom of the stripping chamber.

Transfer of the sample is accomplished by displacement with helium. The helium flow is controlled by a micrometer valve. The helium forces the water sample through the stainless steel tube into the stripping chamber. A toggle valve is located in the helium line to release the pressure in the sample bottle after transfer.

2. Stripping Chamber

The stripping chamber is a glass tube 65 mm. in diameter and 45 cm. tall. It is fitted with a coarse fritted disc at the bottom and a 10 cm. neck, 2 cm. in diameter, at the top. "Purge helium" is introduced just below the fritted disc. It is controlled by a Teflon stopcock and its flow rate is held at 70 ml/min by a Brooks flow control valve.

Just above the fritted disc is the sample inlet. It is connected




Figure 1. Schematic diagram of the dissolved gas analysis system. System is shown in the analyze position.

to one port of a Y-type stopcock. This stopcock allows the operator to purge the line prior to sample transfer, transfer the sample, and later, drain the chamber.

The neck of the chamber is fitted with a ground glass joint. This provides an opening for cleaning and a place to insert the magnetic stirring bar. At the top of the neck is a modified Kjeldahl tip. This breaks any bubbles and thus keeps water from being carried into the rest of the system.

3. Trapping Columns

The traps were constructed of 3/16" stainless steel tubing. The first trap was packed with ten inches of 60/80 mesh activated alumina and the second with a mixture containing $\frac{1}{4}$ activated charcoal and $\frac{3}{4}$ 30/60 mesh 5A molecular sieve. They were connected across the sample loop ports of Perkin-Elmer gas sampling valves (See Figure 2).

Toggle valves were placed on either side of the activated charcoal/ molecular sieve trap. These allowed the trap to be isolated while holding a sample and thus precluded any gas leakage prior to analysis.

4. Backflush Lines

A constant flow of helium had to be maintained across the column in the chromatograph. This was accomplished in that in the trap position, the carrier gas was passing through the gas sampling valve for the activated charcoal/molecular sieve trap to the chromatograph. In the analyze position, the carrier gas backflushed the trapped sample gases to the chromatograph. The flow rate was maintained at 30 ml/min by a Brooks flow control valve.

After the analysis was complete, the activated alumina trap was backflushed with line helium to remove trapped gases. Since this trap was

not analyzed, a cap was placed on the exhaust port when the valve was in the trap position, in order to conserve helium and maintain pressure for stripping. It also kept water from backing up into the system.

B. CALIBRATION SYSTEM

In order to have consistent calibrations, a gas sampling valve with a 1 ml. sample loop was incorporated into the system. This enabled a known gas mixture to be introduced into the trapping system or directly into the chromatograph. A diagram showing the calibration system is shown in Figure 2.

C. GAS CHROMATOGRAPH

A Varian Aerograph Model 600C gas chromatograph was obtained on loan from the Department of Physics and Chemistry. It was equipped with a flame ionization detector (FID), a tube-type electrometer, and a Model 328 isothermal temperature controller.

1. Modifications

The original column was replaced with a four foot, 3/16", stainless steel column packed with 30/60 mesh 5A molecular sieve. Upon conditioning (heating for two hours at 150 °C in a helium atmosphere), this column provided adequate separation of carbon monoxide and methane.

The normal carrier-gas port and injection port on the gas chromatograph were bypassed since the already mixed unknown and carrier gas were entering from the traps, i.e., there was a direct connection of the line from the activated charcoal/molecular sieve trap to the column.

The hydrogen port was also sealed since the hydrogen was introduced prior to a catalyst tube.




Figure 2. Detailed schematic diagram of the calibration system and traps. System is shown in the trap position with a calibration sample being injected into the chromatograph.

D. CATALYST FURNACE

The flame ionization detector is not sensitive to carbon monoxide. Therefore, the carbon monoxide must be converted to methane prior to analysis. This is accomplished by passing the carbon monoxide over a heated nickel catalyst in the presence of hydrogen (Porter and Vollman, 1962).

The catalyst furnace was placed between the analytical column and the detector. It consisted of a 10 cm., $\frac{1}{4}$ ", stainless steel tube in which the catalyst was placed. An aluminum block 7.5 cm. long and 2.5 cm. in diameter was placed around this tube as a heat sink. This assembly was placed flush inside a threaded quartz tube which was wound with a Nichrome wire heater. To prevent fire and provide additional insulation, the heater was placed in a Transite box which was mounted on the side of the chromatograph. The temperature was monitored with a five ohm iron-constantan thermocouple attached to the auxillary terminal of the temperature controller. Temperature control was regulated with a Variac controller.

E. RECORDER

A Varian Model G-14 strip chart recorder was used to record the output of the electrometer. It was set for 1 mv. full scale deflection and run at a chart speed of 1 in./min.

III. EXPERIMENTAL METHODS

A. SAMPLE COLLECTION

Five nearshore stations were taken in kelp beds around the Monterey Peninsula as described in Table 1 and Figure 3. The stations varied from a relatively calm area at Del Monte Beach to areas of extreme turbulence on the exposed coast at Point Pinos and Point Joe. These stations were occupied periodically from 31 October 1972 to 15 December 1972.

Sampling in the nearshore areas was done from a forty foot boat. In order to minimize contamination from the exhaust, the boat was allowed to drift to a stop in the kelp beds prior to sampling. Samples were taken in a Van Dorn type bottle that was rigged with hand lines for lowering and tripping.

Samples were collected in 500 ml. reagent bottles by filling from the bottom with a surgical rubber tube. The bottles were then sealed with a standard taper ground glass stopper. This reduced the possibility of air contamination and outgassing from the sample. If the samples were to be stored before analysis, a small amount of sodium azide (NaN_3) was added to kill any organisms that might alter the dissolved gas concentrations.

In order to have open ocean values to compare with those found in the nearshore habitats, a deep station was taken in the Monterey Canyon aboard R/V Acania (see Table 1). Samples were taken at depths of 0, 5, 15, 30, 50, 75, 100, 200, 500, 700, and 1000 meters using standard Nansen bottles. In addition, a cast was made at 0, 5, 12, 18, and 45 meters for determination of primary productivity (see Rowney, 1973).




Figure 3. Chart showing location of nearshore stations.

Table 1

Seawater Sampling Stations

<u>Station Number</u>	<u>Name</u>	<u>Positions</u>
1	Del Monte Beach	36° 36.3' N 121° 52.4' W
2	Point Cabrillo	36° 37.4' N 121° 54.1' W
3	Point Pinos North	36° 38.3' N 121° 55.4' W
4	Point Pinos South	36° 38.3' N 121° 56.3' W
5	Point Joe	36° 36.8' N 121° 57.3' W
6	R-4 Bell Buoy	36° 37.5' N 121° 54.3' W
7	Monterey Canyon	36° 44.3' N 122° 07.2' W

Transects were taken across Del Monte Beach, from Del Monte Beach to the R-4 buoy, and from Point Cabrillo to the R-4 buoy. These were taken to determine any gradients present.

B. SAMPLE ANALYSIS¹

The sample bottle was connected to the system by a ground glass joint. Helium was introduced above the sample forcing the water through a stainless steel tube to the drain valve. The first few milliliters were discarded to ensure flushing of the transfer line. The stripping chamber, which had been previously drained to the 500 ml. mark, was then filled to the zero mark. This method of transfer minimized contact with the atmosphere and thus reduced the chance of contamination.

"Purge helium" was introduced below the fritted disc and allowed to bubble through the sample for twelve minutes. A magnetic stirring bar in the chamber increased the residence time of the bubbles in the sample. After twelve minutes, no measurable amounts of carbon monoxide or methane were left in the sample and as prior tests showed, no leakage from the cold traps had occurred. Before reaching the traps, the gas passed through a magnesium perchlorate drying agent to remove any water vapor.

Trapping of the gases took place on two series-connected cold traps. They were both maintained at -77°C with an acetone-dry ice bath, in a Dewar flask. The first trap was an activated alumina column which removed any hydrocarbons higher than methane as well as carbon dioxide. The second, a mixture of 1/4 activated charcoal and 3/4 molecular sieve, removed carbon monoxide, methane, and air. In the twelve minute purging time, most

¹ A complete, step-by-step, analysis check list is included in Appendix A.

of the air was bled off the trap and only a small amount of residual oxygen remained. This proved to be no problem since the analytical column in the gas chromatograph provided sufficient separation of these gases.

After the twelve minutes of purging time, isolation valves on either side of the activated charcoal/molecular sieve trap were closed. The acetone-dry ice bath was removed and replaced with one of boiling water. The trap was now backflushed into the analytical column in the gas chromatograph. The activated alumina trap was backflushed to the atmosphere since its contents were not of importance to this experiment.

Retention times for a column temperature of 48°C and a flow rate of 30 ml/min were: air, 1.5 min.; methane, 3.0 min.; carbon monoxide, 4.25 min. Analysis was complete seven minutes after injection of the sample into the gas chromatograph.

To ensure complete conversion of carbon monoxide to methane, the catalyst furnace was held between $300\text{--}320^{\circ}\text{C}$. This also reduced tailing on the carbon monoxide peak.

Figure 4 shows a chromatogram from a sample analysis. The concentration of each gas is proportional to the area under its respective peak. In order for these areas to be meaningful, a method of calibration was needed.

To accomplish this, a calibration gas is used. A calibrated gas mixture of 70.3 ppm methane and 71.1 ppm carbon monoxide in air was obtained from the Naval Research Laboratory, Washington D.C. Preliminary work showed no measurable difference in the results when the gas was introduced into the traps or directly into the gas chromatograph, therefore direct injection was used to conserve time.

Figure 5 shows the results of a calibration run. Now, the response of the system to a known concentration of gas was known and the unknown




Figure 4. Chromatogram from a sample run. Signals from the electro-meter have been attenuated 2:1 for CO and 8:1 for CH₄.

concentrations could be determined by comparing areas. Calibrations were run periodically along with the samples. In addition to calibrating the system, these calibration checks were also used to determine if the catalytic conversion of carbon monoxide to methane was complete.

After the sample was run, the area under each peak was determined in the following manner. The height of the peak and the width at half height were measured with a set of dial calipers. These values were multiplied together to get the raw area; a range and attenuation factor from the electrometer setting was applied to get the effective area. These calculations were carried out on the IBM 360/67 computer. A copy of the program is included in Appendix C.




Figure 5. Chromatogram from a calibration run.

IV. RESULTS

A. OPEN OCEAN DEEP STATION

Station seven (Table 1) was located on the axis of the Monterey Submarine Canyon in 1375 meters of water. An eleven bottle cast to 1000 meters was taken. The profiles from this cast are shown in Figures 6 and 7 and tabulated in Tables 2 and 3.

1. Methane

The methane profile (Figure 6 and Table 2) shows a surface concentration of 1.1×10^{-4} ml/l. This value increases with depth to 50 meters. From 50 to 100 meters it decreases slightly and then more rapidly to 200 meters. It then decreases linearly with depth at a rate of 0.125×10^{-4} ml/l/100 m to 1000 meters.

2. Carbon Monoxide

Figure 7 and Table 3 shows a carbon monoxide concentration of 0.81×10^{-4} ml/l at the surface. This value increases sharply to almost 2×10^{-4} ml/l at 15 meters and then decreases to near surface values at 100 meters. From 100 to 1000 meters, the concentration decreases to only trace amounts.

3. Primary Productivity

Primary productivity measurements made by Rowney (1973) at the same station are shown in Figure 8. Note the relatively high values in the upper 12 meters.

B. TEMPORAL STUDIES

A temporal study of carbon monoxide and methane was conducted in each of the five nearshore habitats. The plots of concentration versus time




Figure 6. Vertical distribution of CH_4 at the Deep Ocean Station in Monterey Canyon.

Table 2

Methane Concentrations in Monterey Canyon

Depth (meters)	Methane Concentration (ml/l)
0	1.013×10^{-4}
0	1.184×10^{-4}
5	1.252×10^{-4}
15	2.342×10^{-4}
15	2.205×10^{-4}
30	2.433×10^{-4}
30	2.632×10^{-4}
50	2.847×10^{-4}
75	2.783×10^{-4}
100	2.752×10^{-4}
200	1.797×10^{-4}
200	1.759×10^{-4}
700	1.037×10^{-4}
1000	0.751×10^{-4}



Figure 7. Vertical distribution of CO₂ at the Deep Ocean Station in Monterey Canyon.

Table 3

Carbon Monoxide Concentrations in Monterey Canyon

Depth (meters)	Carbon Monoxide Concentration (ml/l)
0	0.793×10^{-4}
0	0.836×10^{-4}
5	1.230×10^{-4}
15	2.144×10^{-4}
15	1.818×10^{-4}
30	1.522×10^{-4}
30	1.729×10^{-4}
50	1.391×10^{-4}
75	1.086×10^{-4}
100	0.759×10^{-4}
200	0.836×10^{-4}
200	0.859×10^{-4}
500	0.619×10^{-4}
700	0.436×10^{-4}
1000	trace




Figure 8. Vertical distribution of Primary Productivity in the upper 50 meters of the Deep Ocean Station in Monterey Canyon (from Rowney, 1973).

are found in Figures 9 through 13 and are tabulated in Tables 4 through 8.

Environmental conditions were as follows. The period prior to 31 October 1972 had been clear for several weeks. During the periods 4-17 November and 3-8 December 1972, overcast skies with heavy rains were predominant. The rest of the time, clear skies prevailed. Heavy swell accompanied the periods of rain. This made it impossible to sample stations 3, 4, and 5 during these periods, since it was too rough for the forty foot boat. The surface temperature (Figure 14) decreased from 15°C at the start of the study to 10°C at its conclusion.

All five stations showed high methane concentrations on the first day. These values dropped sharply after the onset of the first storm. Following this storm, the concentrations began to rise, but were again decreased after the second storm. Del Monte Beach showed another increase after this second storm that was not noted at the other stations.

Carbon monoxide did not seem to be affected by the rains as much as methane. It was uniformly low at the start of the study with a general increase throughout the time period. Again, Del Monte Beach showed more variability than the other stations.

C. GRADIENT ANALYSIS

The average of all measurements at each nearshore station was computed and plotted (Figure 15). This provided a gradient analysis for comparison with primary productivity, chlorophyll and nutrient analyses (Rowney 1973).

The methane gradient decreased from Del Monte Beach to Point Cabrillo. It then reversed and showed an increase to the highest value at Point Joe.

Carbon monoxide showed a different pattern. It alternated between decreasing and increasing gradients with a slight overall trend towards higher concentrations at Point Joe.




Figure 9. CH₄ and CO concentrations in the surface waters at Del Monte Beach.

Table 4

Methane and Carbon Monoxide
Concentrations at Del Monte Beach

<u>Date</u>	<u>Methane (ml/l)</u>	<u>Carbon Monoxide (ml/l)</u>
11-03-72	6.829×10^{-4}	0.663×10^{-4}
11-09-72	1.842×10^{-4}	0.546×10^{-4}
11-09-72	1.959×10^{-4}	0.735×10^{-4}
11-14-72	2.648×10^{-4}	0.990×10^{-4}
11-14-72	3.187×10^{-4}	1.088×10^{-4}
11-16-72	2.631×10^{-4}	1.763×10^{-4}
11-28-72	3.102×10^{-4}	2.208×10^{-4}
11-28-72	2.837×10^{-4}	2.318×10^{-4}
12-01-72	4.682×10^{-4}	1.039×10^{-4}
12-07-72	3.669×10^{-4}	1.408×10^{-4}
12-07-72	3.547×10^{-4}	1.345×10^{-4}
12-14-72	5.358×10^{-4}	1.046×10^{-4}
12-14-72	5.277×10^{-4}	1.082×10^{-4}




Figure 10. CH₄ and CO concentrations in the surface waters at Point Cabrillo.

Table 5

Methane and Carbon Monoxide
Concentrations at Point Cabrillo

<u>Date</u>	<u>Methane (ml/l)</u>	<u>Carbon Monoxide (ml/l)</u>
11-03-72	5.273×10^{-4}	0.677×10^{-4}
11-09-72	1.714×10^{-4}	0.942×10^{-4}
11-09-72	1.499×10^{-4}	0.733×10^{-4}
11-14-72	2.323×10^{-4}	0.983×10^{-4}
11-17-72	2.219×10^{-4}	1.209×10^{-4}
11-21-72	2.323×10^{-4}	0.955×10^{-4}
11-21-72	2.152×10^{-4}	1.006×10^{-4}
11-28-72	3.106×10^{-4}	1.066×10^{-4}
11-28-72	3.478×10^{-4}	1.097×10^{-4}
12-15-72	3.117×10^{-4}	1.242×10^{-4}
12-15-72	3.096×10^{-4}	1.305×10^{-4}




Figure 11. CH_4 and CO concentrations in the surface waters at Point Pinos North.

Table 6

Methane and Carbon Monoxide
Concentrations at Point Pinos North

<u>Date</u>	<u>Methane (ml/l)</u>	<u>Carbon Monoxide (ml/l)</u>
10-31-72	4.437×10^{-4}	1.203×10^{-4}
11-21-72	2.014×10^{-4}	1.085×10^{-4}
11-28-72	2.791×10^{-4}	1.531×10^{-4}
11-28-72	2.587×10^{-4}	1.467×10^{-4}
12-15-72	3.267×10^{-4}	1.833×10^{-4}




Figure 12. CH_4 and CO concentrations in the surface waters at Point Pinos South.

Table 7

Methane and Carbon Monoxide

Concentrations at Point Pinos South

<u>Date</u>	<u>Methane (ml/l)</u>	<u>Carbon Monoxide (ml/l)</u>
10-31-72	4.317×10^{-4}	0.875×10^{-4}
11-21-72	2.527×10^{-4}	0.952×10^{-4}
11-21-72	2.635×10^{-4}	1.061×10^{-4}
11-28-72	3.998×10^{-4}	1.288×10^{-4}
11-28-72	3.694×10^{-4}	1.251×10^{-4}
12-15-72	3.481×10^{-4}	1.798×10^{-4}




Figure 13. CH_4 and CO concentrations in the surface waters at Point Joe.

Table 8

Methane and Carbon Monoxide
Concentrations at Point Joe

<u>Date</u>	<u>Methane</u> <u>(ml/l)</u>	<u>Carbon Monoxide</u> <u>(ml/l)</u>
10-31-72	8.524×10^{-4}	1.275×10^{-4}
11-21-72	2.300×10^{-4}	1.034×10^{-4}
11-28-72	4.267×10^{-4}	1.548×10^{-4}
11-28-72	4.501×10^{-4}	1.344×10^{-4}
12-15-72	4.088×10^{-4}	2.109×10^{-4}
12-15-72	4.073×10^{-4}	1.903×10^{-4}




Figure 14. Surface temperature.

D. TRANSECTS

The transect across Del Monte Beach proved most interesting. It started 400 yards east of the Monterey sewage disposal plant outfall and proceeded towards the harbor. Figure 16 and Table 9 show the results of this transect. The initial values of methane and carbon monoxide were low and then increased sharply at the "boil" above the outfall. Concentrations dropped back down west of the "boil" and then started to increase again as the stations got closer to Monterey harbor.

The transects from Del Monte Beach to the R-4 buoy (Figure 17 and Table 10) showed a wide variation in concentrations. On 1 December 1972, the methane decreased slightly to the first station beyond the kelp bed and then increased out to the buoy. Carbon monoxide increased slightly beyond the kelp and then remained fairly constant. On 14 December 1972, the methane followed the same pattern, but the drop in concentration from the kelp bed to the first open water station was much greater. Carbon monoxide seemed to decrease slightly beyond the kelp bed and then build up seaward.

The transect from Point Cabrillo to the R-4 buoy (Figure 18 and Table 11) showed very little change in either gas. Methane increased by $.1 \times 10^{-4}$ ml/l from 3.1×10^{-4} ml/l and carbon monoxide decreased $.4 \times 10^{-4}$ ml/l from 1.3×10^{-4} ml/l.




Figure 15. CH₄ and CO gradients between the five nearshore stations.




Figure 16. CH₄ and CO concentrations for a transect along Del Monte Beach.

Table 9

Methane and Carbon Monoxide
Concentrations for the Transect Along
Del Monte Beach

Date	Location	Methane (ml/l)	Carbon Monoxide (ml/l)
11-16-72	Kelp Edge	2.214×10^{-4}	0.935×10^{-4}
11-16-72	Kelp Edge	2.089×10^{-4}	1.040×10^{-4}
11-16-72	Sewer Outfall	7.053×10^{-4}	2.380×10^{-4}
11-16-72	Sewer Outfall	6.198×10^{-4}	2.191×10^{-4}
11-16-72	Pump House	2.631×10^{-4}	1.763×10^{-4}
11-16-72	Beach lab	1.995×10^{-4}	1.276×10^{-4}
11-16-72	Apartments	2.823×10^{-4}	1.222×10^{-4}
11-16-72	Apartments	2.673×10^{-4}	1.241×10^{-4}
11-16-72	Public Beach	3.161×10^{-4}	1.172×10^{-4}
11-16-72	Public Beach	3.054×10^{-4}	3.054×10^{-4}




Figure 17. CH₄ and CO concentrations from transects from Del Monte Beach to the R-4 Buoy. Solid line is data for 1 December 1972 and dashed line is data for 14 December 1972.

Table 10

Methane and Carbon Monoxide
Concentrations for the Transect from
Del Monte Beach to the R-4 Buoy

Date	Location	Methane (ml/l)	Carbon Monoxide (ml/l)
12-01-72	Station 1	4.682×10^{-4}	1.039×10^{-4}
12-01-72	Kelp Edge	4.517×10^{-4}	1.041×10^{-4}
12-01-72	Kelp Edge	4.609×10^{-4}	1.080×10^{-4}
12-01-72	Open Water 1	4.490×10^{-4}	1.330×10^{-4}
12-01-72	Open Water 1	4.433×10^{-4}	1.389×10^{-4}
12-01-72	Open Water 2	4.965×10^{-4}	1.272×10^{-4}
12-01-72	Open Water 2	5.105×10^{-4}	1.271×10^{-4}
12-01-72	Station 6	5.287×10^{-4}	1.416×10^{-4}
12-01-72	Station 6	5.233×10^{-4}	1.397×10^{-4}
12-14-72	Station 1	5.358×10^{-4}	1.046×10^{-4}
12-14-72	Station 1	5.277×10^{-4}	1.082×10^{-4}
12-14-72	Kelp Edge	4.374×10^{-4}	0.990×10^{-4}
12-14-72	Kelp Edge	4.594×10^{-4}	1.143×10^{-4}
12-14-72	Open Water 1	2.924×10^{-4}	0.856×10^{-4}
12-14-72	Open Water 1	3.120×10^{-4}	0.854×10^{-4}
12-14-72	Open Water 2	3.277×10^{-4}	0.997×10^{-4}
12-14-72	Station 6	3.382×10^{-4}	1.223×10^{-4}




Figure 18. CH₄ and CO concentrations for a transect from Point Cabrillo to the R-4 Bell Buoy.

Table 11

Methane and Carbon Monoxide
Concentrations for the Transect from
Point Cabrillo to the R-4 Buoy

<u>Date</u>	<u>Location</u>	<u>Methane (ml/l)</u>	<u>Carbon Monoxide (ml/l)</u>
12-15-72	Station 2	3.117×10^{-4}	1.242×10^{-4}
12-15-72	Station 2	3.096×10^{-4}	1.305×10^{-4}
12-15-72	Intermediate	3.091×10^{-4}	0.970×10^{-4}
12-15-72	Intermediate	3.136×10^{-4}	1.024×10^{-4}
12-15-72	Station 6	3.231×10^{-4}	0.932×10^{-4}

V. DISCUSSION OF RESULTS

A. PRECISION AND ACCURACY

The precision and accuracy of the gas chromatograph system was checked by running ten consecutive calibration checks. The average of these ten runs was computed as well as the RMS deviation. It was found that to be within plus or minus two RMS deviations, errors as large as 10% could be expected for carbon monoxide and 7.8% for methane.

These errors came mainly from the peak area measurements. First, the determination of a base line proved a problem if there was any drift in the system. To minimize this, the same method of baseline determination was used in each run. This may not eliminate the error, but it should keep it constant.

Area calculation by peak height and width at half height measurement only approximates actual peak area. To solve this problem, either the very careful use of a planimeter, cutting out the peaks and weighing them, or an automatic integrator could be used. These first two unfortunately have the problem of increased analysis time, and the last one, high cost.

B. OPEN OCEAN DEEP STATION

The comparison of Figures 7 and 8 shows a striking correspondence between carbon monoxide concentrations and primary productivity. These results seem to give support to the hypothesis that phytoplankton may be producing carbon monoxide, but this is unexpected and requires experimental verification.

Some anaerobic, methanogenic bacteria are known to convert carbon monoxide to methane (Pine 1971, Jaffe 1970). Figure 19 shows an increase

in both methane and carbon monoxide from the surface to 15 meters. If the carbon monoxide production is related to phytoplankton, and if methane is produced anaerobically in situ (or carried there from an anaerobic source) this could explain the concurrent increase of these gases in the surface layer. From 15-100 meters, the carbon monoxide decreases, but the methane continues to increase. This may show continued bacterial conversion of carbon monoxide to methane below the layer of high productivity, or the advection of a methane rich water mass in the upper 100 meters.

Below 100 meters both gases decrease with depth.

C. TEMPORAL STUDY

The temporal study showed a marked difference between the stations in Monterey Bay (Stations 1 and 2) and those on the exposed coast. Station 1 at Del Monte Beach showed great variability in both methane and carbon monoxide (Figure 9). This was expected since there are many more factors affecting these gases in this environment; sewage disposal plant effluent, pollution from Monterey harbor, and city storm sewer outlets all contribute to the water budget of this station. It is interesting to compare the values of primary productivity with the methane concentrations. They both show marked decrease following the onset of the first storm and then both increase throughout the rest of the study. Carbon monoxide does not show any correlation with primary productivity at this station. The cause for the large jump in carbon monoxide concentration during the period 16-28 November 1972 is unknown. It is possible that this variability in concentrations was present at the other stations and that the more frequent sampling of Del Monte Beach merely showed the transient nature of these gases.

Point Cabrillo (Station 2), still being within the confines of the




Figure 19. Plot of CH₄ vs. CO in the Deep Ocean Station in the Monterey Canyon. Numbers indicate depth in meters.

bay, had characteristics similar to those found at Del Monte Beach. Since it was further removed from the sources of the pollutants at Del Monte Beach, the variability was not as great. There was still a parallel trend between methane and primary productivity, and none noted for carbon monoxide.

Station 3 at Point Pinos North is subject to the heavy surf action from oceanic waves. Like stations 1 and 2, it, too, showed close correlation between methane and primary productivity, but it also showed a trend between carbon monoxide and primary productivity after the heavy rains.

Station 4 was located just off the Pacific Grove sewage disposal plant outfall at Point Pinos. Here, the methane-primary productivity and the post storm carbon monoxide-primary productivity correlations were both good. It was interesting to note that little or no influence from the sewage effluent was noted in the kelp bed off shore, while the rocks near the outfall appeared to be devoid of life. This probably shows the diluting effect on the heavily chlorinated sewage of the turbulent mixing from the surf in this area.

Station 5 at Point Joe initially showed exceptionally high methane concentrations. Following the first storm, this was reduced to values comparable to the other four stations. Following the rains, it increased more rapidly than any other station. These high methane concentrations seem to indicate a methane source near Point Joe. It is very possible that this source is the Pebble Beach sewage outfall, located just south of Point Joe, where apparently untreated sewage is dumped directly into the ocean.

When the methane concentration was exceptionally high, primary productivity was low. This does not follow the pattern set by the other four

stations. It is possible that phytoplankton growth is inhibited when methane concentrations reach a certain toxic level, or both may be affected by a third factor. After the rains, and subsequent decrease in methane concentrations, the correlation between methane and primary productivity was again apparent.

Carbon monoxide and primary productivity showed very good correlations throughout the sampling period at this station.

D. GRADIENT ANALYSIS

The gradient analysis (Figure 15) indicates the possibility of methane sources at Del Monte Beach and Point Joe. Since the high methane gradients exist at or near sewage disposal plant outfalls, this supports the hypothesis that methane can be used as a tracer for sewage effluent.

The carbon monoxide gradient was not as dramatic as that for methane. It also showed the highest value at Point Joe. An examination of the plant population of Point Joe may help explain this. Stations 1 through 4 are predominantly Macrocystis pyrifera while station 5 is mainly Nereocystis leutkeana. Loewus and Delwiche (1963) have shown that Nereocystis leutkeana produces three times as much carbon monoxide as Macrocystis pyrifera. Therefore, one would expect higher carbon monoxide concentrations at Point Joe than at other stations. A closer examination of the macroalgae at each station might help to explain the variation in the carbon monoxide gradients.

The open ocean value of 1.1×10^{-4} ml/l measured in the Monterey Canyon is 2.4 times the equilibrium concentration of methane in seawater (assuming methane content of air is 1.24 ppm). Similarly, the carbon monoxide concentration of 0.81×10^{-4} ml/l is 22.5 times the equilibrium concentration (assuming the highest reported oceanic partial pressure for

carbon monoxide of 0.17 ppm). The average concentration for both carbon monoxide and methane at each station was considerably higher than the oceanic value. Therefore, it is likely that these kelp beds are sources of these gases to the atmosphere.

E. TRANSECTS

The transects from Del Monte Beach to the R-4 buoy showed the effect of the rains on these gases. Before the rains, the concentrations of both gases in the kelp bed and in the open water were high. After the rains, the values in the kelp were high, but the open water values were decreased substantially. This may show the effect of the kelp as an inhibitor to the mixing process.

The transect from Point Cabrillo to the R-4 buoy showed essentially constant, low methane concentrations. This transect was taken after the rains, and since no methane source near Point Cabrillo was indicated in the gradient analysis, this type of profile could be expected.

The carbon monoxide, on the other hand, showed a decrease seaward. If, indeed, the macroalgae are producing carbon monoxide, this decrease away from the kelp bed could be expected.

Since the gradient analysis indicated a source of methane at Del Monte Beach, a transect was taken there to determine the source of the pollutant (Figure 16). As was expected, extremely high methane values were found in the "boil" above the sewage outfall. Since Monterey does not use an anaerobic treatment process, the source of this methane raised an interesting question.

One possibility was that organic matter was settling out around the outfall. This could create anaerobic conditions and thus generate high concentrations of methane. This idea was abandoned after talking with divers who had frequented the area.

The second premise was that the methane was already present before the sewage reached the treatment plant. This was substantiated by some early attempts to analyze tap water. The city water had so much methane in it that the electrometer in the gas chromatograph was immediately saturated and no value could be obtained.

There was also an indication that the harbor was also a source of both carbon monoxide and methane. With the leakage of petroleum products and the exhaust from power boats, it is no wonder that this was observed.

VI. SUMMARY

Results from the open ocean station and several nearshore stations show a possible correlation between carbon monoxide and primary productivity in this relatively pollution-free environment. Methane was also shown to be present in the upper 100 meters, showing a maximum at about 50 meters. This may indicate biological production of this gas in an oxygen rich environment.

At the nearshore stations, concentrations of methane and carbon monoxide were both far above equilibrium and open ocean values. It was shown that methane concentrations were highest in the vicinity of sewage outfalls and that the source of this gas may be the city water supply. Carbon monoxide concentrations may very well be dependent on the type of plant life in the surrounding waters.

Rain was shown to act as a depressant for methane concentrations and primary productivity, but had little effect on carbon monoxide. Methane in very high concentrations appeared to act as a poison to phytoplankton since primary productivity dropped dramatically in methane rich waters.

The transects showed that methane was an effective tracer for sewage disposal plant effluent and that the kelp seemed to slow the diffusion and mixing of pollutants.

From equilibrium considerations, the waters of Monterey Bay were found to be supersaturated with carbon monoxide and methane. The highest concentrations were, for the most part, located in the kelp beds. These results indicate that, at least locally, the ocean is a source of carbon monoxide and methane in the atmosphere.

VII. RECOMMENDATIONS

Further work with this system could prove valuable in the field of air-sea interaction. By incorporating an air sampling loop, direct measurements of interfacial gradients for a variety of components could be made. It would have been especially helpful in the present study to have known the atmospheric concentrations of these gases.

Due to the limitations of the gas chromatograph used, the hydrocarbons higher than methane that were trapped were not analyzed. In the future, a useful addition to the system would be a dual channel, dual detector gas chromatograph. This would allow simultaneous analysis of a wide variety of organics. The addition of a self-integrating recorder would provide the capability of making on-station, real-time measurements of these dissolved gases.

It is recommended that further work on carbon monoxide and methane be pursued in the Monterey Submarine Canyon. Paucity of ship time aboard R/V Acania precluded further investigation of this area during this study.

APPENDIX A

Analysis Procedures

Sample Transfer

1. Bottle on.
2. Open drain valve to sample bottle to remove old sample from line.
3. Turn drain valve to fill stripping chamber.
4. Turn transfer valve.
5. At 100 ml. turn off transfer valve.
6. Turn drain valve off at zero.
7. Open pressure release and close again.

Stripping

1. Place cold traps.
2. Valve T1 to Trap.
3. Valve T2 to Trap.
4. Trap/Anal valve to Trap.
5. Cal valve to Cal Fill.
6. Trap/Bypass to Trap.
7. Open trap isolation valves.
8. Ensure cap is on valve T1.
9. Open helium purge and start timer.
10. Turn on magnetic stirring bar.
11. Check exhaust flow (13).
12. Close trap isolation valves at 720 sec.
13. Drain 25 - 50 ml. from chamber.

14. Switch Trap/Bypass valve to Bypass.
15. Leave helium flow on.

Analysis

1. Remove cold traps.
2. Place hot water on Trap 2.
3. Warm for one minute.
4. Place Trap/Anal valve to Anal.
5. Set range and attenuation.
6. Zero recorder using Bucking Voltage (obtain baseline).
7. Turn recorder on Low (1"/min.)
8. Turn valve T2 to anal at reference line on recorder.
9. Analysis is complete in seven minutes.

Clean up

1. Drain stripping chamber to about 475 ml.
2. Turn off purge helium.
3. Drain to 500 ml.
4. Place hot water on Trap 1.
5. Remove cap from T1.
6. Switch T1 to Anal.
7. Warm for 1 minute.
8. Replace cap on T1.
9. Remove hot water.
10. Remove sample bottle.

APPENDIX B

Procedures for Blanks and Calibrations

Calibration (direct injection)

Valve T1 - Trap position.

Valve T2 - Trap position

Anal/Trap - Trap position

Cal valve - Cal Fill position

Trap/Bypass - Bypass position

Fill cal loop

Cal valve - Cal inj. position

Calibration (through traps)

Valve T1 - Trap position

Valve T2 - Trap position

Anal/Trap - Anal position

Cal valve - Cal Fill position

Trap/Bypass - Trap position

Fill Cal Loop

Cal valve - Cal inj. position

Run as if it were a sample, follow stripping and analysis procedure as in Appendix A.

Blank (Run before a series of samples)

Valve T1 - Trap position

Valve T2 - Trap position

Trap/Bypass - Trap position

Cal valve - not important

Run degassed sample, follow stripping and analysis procedures in Appendix A to clear system or check for purge gas contamination.

Appendix C

Program for Computing Concentrations

```

DIMENSION H(2),CH(2),W(2),CW(2),A(2),CA(2),CV(2),VOL(2),CONC(2),
1COUNT(2),CCOUNT(2),LOC(5),X(30),Y(30),DEPTH(30)
CV(1)=70.3E-6
CV(2)=71.1E-6
J=1
K=1000
WRITE (6,102)
102 FORMAT (T12,'DATE',12X,'LOCATION',12X,'BOT', NO.,12X,'DEPTH',12X,
1,METHANE',12X,'CARBON MONOXIDE',//)
1000 READ (5,100)END=9999) IDATE,IBOT,LOC,I,IDEPTH,CH(I),CW(I),CRNG,
1CATT,H(I),W(I),RNG,ATT,SAMP
100 FFORMAT (I6,I4,5A4,I1,I4,8F5.0,F5.3)
A(I)=H(I)*W(I)
CA(I)=CH(I)*CW(I)
COUNT(I)=A(I)*RNG*ATT
CCOUNT(I)=CA(I)*CRNG*CATT
VOL(I)=(CV(I)*COUNT(I))/(CCOUNT(I))
CONC(I)=VOL(I)/SAMP
IF (I.EQ.1) GO TO 1000
WRITE (6,101)IDATE,LOC,IBOT,IDEPTH,CONC(1),CONC(2)
101 FORMAT ('0',T11,I6,T22,5A4,T50,I4,T69,I4,T85,1PE10.3,T107,1PE10.3)
9999 GO TO 1000
STOP
END

```


DISSOLVED GASES DATA SHEET

Raw Data

[illegible]

DISSOLVED GASES DATA SHEET

64

DISSOLVED GASES DATA SHEET

R.V. Aradice			9			071100 NOV 72			09 1930 NOV 72			H. J. J. J. J.		
VESSEL			CRUISE NO.			DATE/TIME COLLECTED			DATE/TIME ANALYZED			ANALYST		
DATE	BOTT. NO.	LOCATION	DEPTH (M)	H CAL	W CAL	RANGE CAL	ATTEN CAL	H COMP	W COMP	RANGE COMP	ATTEN COMP	VOLUME (L)		
11/9/72	11	MONTREY CANYON	75	2467	482	1.0	1.0	2228	528	1.0	4.0	500		
	11		75	1529	758	1.0	2.0	543	815	1.0	4.0	500		
	12		75	2467	482	1.0	2.0	2403	540	1.0	4.0	500		
	12		75	1529	758	1.0	2.0	2993	793	1.0	4.0	500		
	13		75	2467	482	1.0	2.0	2177	553	1.0	4.0	500		
	13		75	1529	758	1.0	2.0	1383	820	1.0	2.0	500		
	14		75	2467	482	1.0	2.0	2317	523	1.0	4.0	500		
	14		75	1529	758	1.0	2.0	2331	771	1.0	2.0	500		
	15		75	2467	482	1.0	2.0	1102	505	1.0	8.0	500		
	15		75	1529	758	1.0	2.0	1853	761	1.0	2.0	500		
	16		75	2467	482	1.0	2.0	2108	488	1.0	4.0	500		
	16		75	1529	758	1.0	2.0	1590	780	1.0	2.0	500		
	17		75	2467	482	1.0	2.0	1915	487	1.0	4.0	500		
	17		75	1529	758	1.0	2.0	1880	788	1.0	2.0	500		
	18		75	2467	482	1.0	2.0	1934	512	1.0	4.0	500		
	18		75	1529	758	1.0	2.0	2281	766	1.0	2.0	500		
	19		75	2467	482	1.0	2.0	1886	518	1.0	4.0	500		
	19		75	1529	758	1.0	2.0	2576	768	1.0	2.0	500		

DISSOLVED GASES DATA SHEET

VESSEL		CRUISE NO.		DATE/TIME COLLECTED		DATE/TIME ANALYZED		ANALYST				
K. V. Albatross		7		071100 Nov 72		101700 Nov 72		J. H. S. J. H. S.				
DATE	BOTT. NO.	LOCATION	DEPTH (M)	H CAL	W CAL	RANGE CAL	ATTEN CAL	H COMP	W COMP	RANGE COMP	ATTEN COMP	VOLUME (L)
11/07/72	20	MONTREUX Canyon	52367	442	442	442	442	442	442	442	442	442
	21		4412	736	736	736	736	736	736	736	736	736
	22		4412	442	442	442	442	442	442	442	442	442
	23		4476	750	750	750	750	750	750	750	750	750
	24		4412	442	442	442	442	442	442	442	442	442
	25		4412	736	736	736	736	736	736	736	736	736
	26		4412	442	442	442	442	442	442	442	442	442
	27		4412	736	736	736	736	736	736	736	736	736
	28		4412	442	442	442	442	442	442	442	442	442
	29		4412	736	736	736	736	736	736	736	736	736
	30		4412	442	442	442	442	442	442	442	442	442
	31		4412	736	736	736	736	736	736	736	736	736
	32		4412	442	442	442	442	442	442	442	442	442
	33		4412	736	736	736	736	736	736	736	736	736
	34		4412	442	442	442	442	442	442	442	442	442
	35		4412	736	736	736	736	736	736	736	736	736
	36		4412	442	442	442	442	442	442	442	442	442
	37		4412	736	736	736	736	736	736	736	736	736
	38		4412	442	442	442	442	442	442	442	442	442
	39		4412	736	736	736	736	736	736	736	736	736
	40		4412	442	442	442	442	442	442	442	442	442
	41		4412	736	736	736	736	736	736	736	736	736
	42		4412	442	442	442	442	442	442	442	442	442
	43		4412	736	736	736	736	736	736	736	736	736
	44		4412	442	442	442	442	442	442	442	442	442
	45		4412	736	736	736	736	736	736	736	736	736
	46		4412	442	442	442	442	442	442	442	442	442
	47		4412	736	736	736	736	736	736	736	736	736
	48		4412	442	442	442	442	442	442	442	442	442
	49		4412	736	736	736	736	736	736	736	736	736
	50		4412	442	442	442	442	442	442	442	442	442
	51		4412	736	736	736	736	736	736	736	736	736
	52		4412	442	442	442	442	442	442	442	442	442
	53		4412	736	736	736	736	736	736	736	736	736
	54		4412	442	442	442	442	442	442	442	442	442
	55		4412	736	736	736	736	736	736	736	736	736
	56		4412	442	442	442	442	442	442	442	442	442
	57		4412	736	736	736	736	736	736	736	736	736
	58		4412	442	442	442	442	442	442	442	442	442
	59		4412	736	736	736	736	736	736	736	736	736
	60		4412	442	442	442	442	442	442	442	442	442
	61		4412	736	736	736	736	736	736	736	736	736
	62		4412	442	442	442	442	442	442	442	442	442
	63		4412	736	736	736	736	736	736	736	736	736
	64		4412	442	442	442	442	442	442	442	442	442
	65		4412	736	736	736	736	736	736	736	736	736
	66		4412	442	442	442	442	442	442	442	442	442
	67		4412	736	736	736	736	736	736	736	736	736
	68		4412	442	442	442	442	442	442	442	442	442
	69		4412	736	736	736	736	736	736	736	736	736
	70		4412	442	442	442	442	442	442	442	442	442
	71		4412	736	736	736	736	736	736	736	736	736
	72		4412	442	442	442	442	442	442	442	442	442
	73		4412	736	736	736	736	736	736	736	736	736
	74		4412	442	442	442	442	442	442	442	442	442
	75		4412	736	736	736	736	736	736	736	736	736
	76		4412	442	442	442	442	442	442	442	442	442
	77		4412	736	736	736	736	736	736	736	736	736
	78		4412	442	442	442	442	442	442	442	442	442
	79		4412	736	736	736	736	736	736	736	736	736
	80		4412	442	442	442	442	442	442	442	442	442
	81		4412	736	736	736	736	736	736	736	736	736
	82		4412	442	442	442	442	442	442	442	442	442
	83		4412	736	736	736	736	736	736	736	736	736
	84		4412	442	442	442	442	442	442	442	442	442
	85		4412	736	736	736	736	736	736	736	736	736
	86		4412	442	442	442	442	442	442	442	442	442
	87		4412	736	736	736	736	736	736	736	736	736
	88		4412	442	442	442	442	442	442	442	442	442
	89		4412	736	736	736	736	736	736	736	736	736
	90		4412	442	442	442	442	442	442	442	442	442
	91		4412	736	736	736	736	736	736	736	736	736
	92		4412	442	442	442	442	442	442	442	442	442
	93		4412	736	736	736	736	736	736	736	736	736
	94		4412	442	442	442	442	442	442	442	442	442
	95		4412	736	736	736	736	736	736	736	736	736
	96		4412	442	442	442	442	442	442	442	442	442
	97		4412	736	736	736	736	736	736	736	736	736
	98		4412	442	442	442	442	442	442	442	442	442
	99		4412	736	736	736	736	736	736	736	736	736
	100		4412	442	442	442	442	442	442	442	442	442

DISSOLVED GASES DATA SHEET

67

DISSOLVED GASES DATA SHEET

40' Boat		11		14 0700 Nov 72		14 1000 Nov 72		J. Studebaker					
VESSEL		CRUISE NO.		DATE/TIME COLLECTED		DATE/TIME ANALYZED		ANALYST					
DATE	BOTT. NO.	LOCATION	C	DEPTH (M)	H CAL	W CAL	RANGE CAL	ATTEN CAL	H COMP	W COMP	RANGE COMP	ATTEN COMP	VOLUME (L)
11/23/72	10			10	1786	484	1.0	2.0	1606	1651	1.0	1.0	1500
11/23/72	11	HOPKINS MARINE STA		10	1786	739	1.0	2.0	2638	1858	1.0	1.0	1500
	12			10	1786	484	1.0	2.0	1409	519	1.0	4.0	1500
	13			10	1786	739	1.0	2.0	1583	714	1.0	1.0	1500
	14			10	1786	484	1.0	2.0	1514	494	1.0	4.0	1500
	15	DEL MONTE REACH		10	1786	739	1.0	2.0	1549	762	1.0	1.0	1500
	16			10	1786	484	1.0	2.0	1783	505	1.0	4.0	1500
	17			10	1786	739	1.0	2.0	1723	749	1.0	1.0	1500
	18			10	1786	484	1.0	2.0					
	19			10	1786	739	1.0	2.0					
	20			10	1786	484	1.0	2.0					
	21			10	1786	739	1.0	2.0					
	22			10	1786	484	1.0	2.0					
	23			10	1786	739	1.0	2.0					
	24			10	1786	484	1.0	2.0					
	25			10	1786	739	1.0	2.0					
	26			10	1786	484	1.0	2.0					
	27			10	1786	739	1.0	2.0					
	28			10	1786	484	1.0	2.0					
	29			10	1786	739	1.0	2.0					
	30			10	1786	484	1.0	2.0					

DISSOLVED GASES DATA SHEET

69

DISSOLVED GASES DATA SHEET

70

DISSOLVED GASES DATA SHEET

71

U. S. NAVAL POSTGRADUATE SCHOOL
DEPARTMENT OF OCEANOGRAPHY

DISSOLVED GASES DATA SHEET

VESSEL		CRUISE NO.		DATE/TIME COLLECTED		DATE/TIME ANALYZED		ANALYST				
40' R/V		14		21 0900 NOV 72		21 1100 NOV 72		J. W. L.				
DATE	BOTT. NO.	LOCATION	DEPTH (M)	H CAL	W CAL	RANGE CAL	ATTEN CAL	H COMP	W COMP	RANGE COMP	ATTEN COMP	VOLUME (L)
11/21/72	1	POINT JOE	1	19.50	439	1.0	2.0	1477	474	1.0	4.0	1.500
	2		2	12.81	678	1.0	2.0	1894	799	1.0	1.0	1.500
	3		1	19.50	439	1.0	2.0	1273	516	1.0	4.0	1.500
	4		2	12.81	678	1.0	2.0	1273	794	1.0	4.0	1.500
	5	POINT PINOS SOUTH	1	19.50	439	1.0	2.0	1637	470	1.0	4.0	1.500
	6		2	12.81	678	1.0	2.0	1680	697	1.0	1.0	1.500
	7		1	19.50	439	1.0	2.0	1736	462	1.0	4.0	1.500
	8		2	12.81	678	1.0	2.0	1878	690	1.0	1.0	1.500
	9	POINT PINOS NORTH	1	19.50	439	1.0	2.0	1251	490	1.0	4.0	1.500
	10		2	12.81	678	1.0	2.0	1910	694	1.0	1.0	1.500
	11		1	19.50	439	1.0	2.0	---	---	1.0	4.0	1.500
	12		2	12.81	678	1.0	2.0	---	---	1.0	1.0	1.500
	13	HOPKINS MARINE STA	1	19.50	439	1.0	2.0	1420	498	1.0	4.0	1.500
	14		2	12.81	678	1.0	2.0	1721	687	1.0	1.0	1.500
	15		1	19.50	439	1.0	2.0	1362	481	1.0	4.0	1.500
	16		2	12.81	678	1.0	2.0	1739	707	1.0	1.0	1.500
	17	DELA MONTE BEACH	1	---	---	1.0	2.0	---	---	1.0	---	1.500
	18		2	---	---	1.0	2.0	---	---	1.0	---	1.500
	19		1	---	---	1.0	2.0	---	---	1.0	---	1.500
	20		2	---	---	1.0	2.0	---	---	1.0	---	1.500
	21		1	---	---	1.0	2.0	---	---	1.0	---	1.500
	22		2	---	---	1.0	2.0	---	---	1.0	---	1.500

DISSOLVED GASES DATA SHEET

VESSEL		CRUISE NO.		DATE/TIME COLLECTED		DATE/TIME ANALYZED		ANALYST																	
DATE		BOTT. NO.		LOCATION		DEPTH (M)		H CAL		W CAL		RANGE CAL		ATTEN CAL		H COMP		W COMP		RANGE COMP		ATTEN COMP		VOLUME (L)	
11/28/72	1	1	1	POINT JONES	1	18.69	455	1.0	2.0	2605	493	1.0	4.0	1.500											
	1	1	2		2	12.32	677	1.0	3.0	627	724	1.0	4.0	1.500											
	2	1	1		1	18.60	455	1.0	2.0	2546	476	1.0	4.0	1.500											
	2	2	1		2	12.32	677	1.0	3.0	2196	718	1.0	4.0	1.500											
	2	2	2	POINT PINOS SOUTH	1	18.60	455	1.0	2.0	2549	472	1.0	4.0	1.500											
	3	2	1		2	12.32	677	1.0	3.0	542	697	1.0	4.0	1.500											
	4	2	1		1	19.22	440	1.0	2.0	2309	483	1.0	4.0	1.500											
	4	2	2		2	12.65	684	1.0	2.0	2144	710	1.0	4.0	1.500											
	5	2	1	POINT PINOS NORTH	1	19.22	440	1.0	2.0	1729	488	1.0	4.0	1.500											
	5	2	2		2	12.65	684	1.0	2.0	2662	709	1.0	4.0	1.500											
	6	2	1		1	19.22	440	1.0	2.0	1684	462	1.0	4.0	1.500											
	6	2	2		2	12.65	684	1.0	2.0	2569	695	1.0	4.0	1.500											
	7	2	1	HOPKINS MARINE STR	1	19.22	440	1.0	2.0	1950	479	1.0	4.0	1.500											
	7	2	2		2	12.65	684	1.0	2.0	1800	721	1.0	4.0	1.500											
	8	2	1		1	18.37	450	1.0	2.0	2166	473	1.0	4.0	1.500											
	8	2	2		2	12.35	680	1.0	2.0	1810	716	1.0	4.0	1.500											
	9	2	1	DELA MONTE BEACH	1	18.37	450	1.0	2.0	1932	472	1.0	4.0	1.500											
	9	2	2		2	12.35	680	1.0	2.0	3786	689	1.0	4.0	1.500											
	10	2	1		1	18.37	450	1.0	2.0	1821	458	1.0	4.0	1.500											
	10	2	2		2	12.35	680	1.0	2.0	1039	678	1.0	4.0	1.500											

DISSOLVED GASES DATA SHEET

VESSEL		CRUISE NO.		DATE/TIME COLLECTED		DATE/TIME ANALYZED		ANALYST				
40' Boat		16		01 0900 Dec 72		01 1400 Dec 72		J. W. J. J.				
DATE	BOTT. NO.	LOCATION	DEPTH (M)	H CAL	W CAL	RANGE CAL	ATTEN CAL	H COMP	W COMP	RANGE COMP	ATTEN COMP	VOLUME (L)
120172	1	DEL MONTE REACH	1	1274.1	467.1	1.0	2.0	1274.1	526.1	1.0	4.0	1.500
	2		2	1274.1	468.1	1.0	2.0	955.8	719.6	1.0	4.0	1.500
	3		3	1274.1	467.1	1.0	2.0	289.2	495.1	1.0	4.0	1.500
	4		4	1274.1	468.1	1.0	2.0	162.6	780.1	1.0	4.0	1.500
	5	DEL MONTE (QUARTER)	5	1274.1	467.1	1.0	2.0	288.9	478.1	1.0	4.0	1.500
	6		6	1274.1	468.1	1.0	2.0	175.7	723.1	1.0	4.0	1.500
	7		7	1274.1	467.1	1.0	2.0	272.3	491.1	1.0	4.0	1.500
	8		8	1274.1	468.1	1.0	2.0	174.9	710.1	1.0	4.0	1.500
	9	DEL MONTE-CALCOFI	9	1274.1	467.1	1.0	2.0	243.5	522.1	1.0	4.0	1.500
	10		10	1274.1	468.1	1.0	2.0	205.9	743.1	1.0	4.0	1.500
	11		11	1274.1	467.1	1.0	2.0	261.9	491.1	1.0	4.0	1.500
	12		12	1274.1	468.1	1.0	2.0	213.3	749.1	1.0	4.0	1.500
	13	CALCOFI 1 (QUARTER)	13	1274.1	467.1	1.0	2.0	298.8	482.1	1.0	4.0	1.500
	14		14	1274.1	468.1	1.0	2.0	206.5	708.1	1.0	4.0	1.500
	15		15	1274.1	467.1	1.0	2.0	303.5	491.1	1.0	4.0	1.500
	16		16	1274.1	468.1	1.0	2.0	198.4	741.1	1.0	4.0	1.500
	17	CALCOFI 1	17	1274.1	467.1	1.0	2.0	324.2	476.1	1.0	4.0	1.500
	18		18	1274.1	468.1	1.0	2.0	224.9	728.1	1.0	4.0	1.500
	19		19	1274.1	467.1	1.0	2.0	225.0	470.1	1.0	4.0	1.500
	20		20	1274.1	468.1	1.0	2.0	221.4	730.1	1.0	4.0	1.500

DISSOLVED GASES DATA SHEET

75

DISSOLVED GASES DATA SHEET

76

DISSOLVED GASES DATA SHEET

40' Boat		21		15 0000 (00:72)		15 1200 (12:72)		ANALYST					
VESSEL		CRUISE NO.		DATE/TIME COLLECTED		DATE/TIME ANALYZED		ANALYST					
DATE	BOTT. NO.	LOCATION		DEPTH (M)	H CAL	W CAL	RANGE CAL	ATTEN CAL	H COMP	W COMP	RANGE COMP	ATTEN COMP	VOLUME (L)
121572	11	POINT JOE		1	3531.	454.	11.0	11.0	3321.	503.	11.0	11.0	500
	12			2	3419.	695.	11.0	11.0	3526.	707.	11.0	11.0	500
	13			1	3531.	454.	11.0	11.0	3163.	537.	11.0	4.0	500
	14			2	3419.	695.	11.0	11.0	3009.	750.	11.0	11.0	500
	15	POINT PINOS SOUTH		1	3016.	464.	11.0	2.0	3199.	570.	11.0	4.0	500
	16			2	3285.	668.	11.0	2.0	3016.	799.	11.0	1.0	500
	17			1	3016.	464.	11.0	2.0	3407.	493.	11.0	4.0	500
	18	POINT PINOS NORTH		2	3285.	668.	11.0	2.0	3006.	723.	11.0	1.0	500
	19			1	3021.	461.	11.0	2.0	3191.	494.	11.0	4.0	500
	20			1	3363.	703.	11.0	2.0	3440.	718.	11.0	1.0	500
	21			1	3021.	461.	11.0	2.0	3081.	475.	11.0	4.0	500
	22	HOPKINS MARINE STA.		2	3363.	703.	11.0	2.0	3230.	707.	11.0	1.0	500
	23			1	3039.	467.	11.0	2.0	3180.	482.	11.0	4.0	500
	24			1	3348.	719.	11.0	2.0	3258.	750.	11.0	1.0	500
	25			1	3039.	467.	11.0	2.0	2096.	478.	11.0	4.0	500
	26			2	3348.	719.	11.0	2.0	3491.	714.	11.0	1.0	500
	27	HOPKINS-CALCOFILL		1	3997.	465.	11.0	2.0	2131.	479.	11.0	4.0	500
	28			1	3361.	706.	11.0	2.0	1886.	695.	11.0	1.0	500
	29			1	3997.	465.	11.0	2.0	2131.	486.	11.0	4.0	500
	30			1	3361.	706.	11.0	2.0	1887.	735.	11.0	1.0	500

DISSOLVED GASES DATA SHEET

78

DISSOLVED GASES DATA SHEET

79

BIBLIOGRAPHY

- Barham, E. G., "Siphonophores and the Deep Scattering Layer," Science, v. 140 (3568), p. 826-828, May 1963.
- Chapman, D. J., and R. D. Tocher, "Occurrence and Production of Carbon Monoxide in Some Brown Algae," Can. J. Bot., v. 44, p. 1438-1442, 1966.
- Delwiche, C. C., "Carbon Monoxide Production and Utilization by Higher Plants," Ann. N. Y. Acad. Sci., v. 174, p. 116, 1970.
- Jaffe, L. S., "The Global Balance of Carbon Monoxide" in, Global Effects of Environmental Pollution, 1968, S.F. Singer, ed., Springer-Verlag, p. 34-49, 1970.
- Junge, C., W. Seiler, R. Bock, K. D. Greese, and F. Radler, "Über die CO-Produktion von Mikroorganismen," Naturwissenschaften, v. 58 (7), p. 362-363, 1971.
- Loewus, M. W., and C. C. Delwiche, "Carbon Monoxide Production by Algae," Plant Physiol., v. 38 (4), p. 371-374, July 1963.
- Pickwell, G. V., "The physiology of Carbon Monoxide Production by Deep Sea Coelenterates: Causes and Consequences," Ann. N. Y. Acad. Sci., v. 174, p. 102, 1970.
- Pickwell, G. V., E. G. Barham, and J. W. Wilton, "Carbon Monoxide Production by a Bathypelagic Siphonophore," Science, v. 144 (1620), p. 860-862, May 1964.
- Pine, M. J., "The Methane Fermentations," in, Anaerobic Biological Treatment Processes, F. G. Pohland, American Chemical Society, p. 1-10, 1971.
- Porter, K. and D. H. Volman, "Flame Ionization Detection of Carbon Monoxide for Gas Chromatographic Analysis," Anal. Chem., v. 34 (7), p. 748-749, June 1962.
- Rowney, J. V., Gradient Analysis of Phytoplankton Productivity and Chemical Parameters in Polluted and Other Nearshore Habitats, Master's Thesis, Naval Postgraduate School, Monterey, California, 1973.
- Swinnerton, J.W., V. J. Linnenbom, and C. H. Cheek, "Determination of Dissolved Gases in Aqueous Solutions by Gas Chromatography," Anal. Chem., v. 34 (4) p. 483-485, April 1962.
- Swinnerton, J.W., V. J. Linnenbom, and C. H. Cheek, "Revised Sampling Procedure for Determination of Dissolved Gases in Solution by Gas Chromatography," Anal. Chem., v. 34 (11), p. 1509, October 1962.

Swinnerton, J. W., V. J. Linnenbom, and C. H. Cheek, "A Sensitive Gas Chromatographic Method for Determining Carbon Monoxide in Sea Water," Limnol. Oceanog., v. 13 (1), p. 193-195, January 1968.

Swinnerton, J. W., V. J. Linnenbom, and C. H. Cheek, "Distribution of Methane and Carbon Monoxide Between the Atmosphere and Natural Waters," Env. Sci. Tech., v. 3, p. 836-838, September, 1969.

Swinnerton, J. W., V. J. Linnenbom, and R. A. Lamontagne, "The Ocean: A Natural Source of Carbon Monoxide," Science, v. 167 p. 984-986, February, 1970.

Wittenberg, J. B., "The Source of Carbon Monoxide in the Float of the Portuguese Man-of-War, *Physalia physalis* L.," J. Exp. Biol., v. 37 (4), p. 698-705, December 1960.

INITIAL DISTRIBUTION LIST

	No. Copies
1. Defense Documentation Center Cameron Station Alexandria, Virginia 22314	2
2. Library, Code 0212 Naval Postgraduate School Monterey, California 93940	2
3. Department of Oceanography Naval Postgraduate School Monterey, California 93940	3
4. Oceanographer of the Navy The Madison Building 732 North Washington Street Alexandria, Virginia 22314	1
5. Dr. Ned Ostenso Code 480 D Office of Naval Research Arlington, Virginia 22217	1
6. Dr. John W. Swinnerton Chemical Oceanography Branch Ocean Sciences Division Naval Research Laboratory Washington, D. C. 20390	1
7. Dr. Eugene D. Traganza Code 58Tg Department of Oceanography Naval Postgraduate School Monterey, California 93940	7
8. Lieutenant James T. Welch U. S. Naval Facility NPO 558 Patrick AFB, Florida 32925	1

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)

Naval Postgraduate School
Monterey, California 93940

2a. REPORT SECURITY CLASSIFICATION

Unclassified

2b. GROUP

3. REPORT TITLE

Gradient Analysis of Carbon Monoxide and Methane in Polluted
and Other Nearshore Habitats

4. DESCRIPTIVE NOTES (Type of report and, inclusive dates)

Master's Thesis (March, 1973).

5. AUTHOR(S) (First name, middle initial, last name)

James Taylor Welch

6. REPORT DATE

March 1973

7a. TOTAL NO. OF PAGES

84

7b. NO. OF REFS

17

8. CONTRACT OR GRANT NO.

9a. ORIGINATOR'S REPORT NUMBER(S)

9. PROJECT NO.

9b. OTHER REPORT NO(S) (Any other numbers that may be assigned
this report)

10. DISTRIBUTION STATEMENT

Approved for public release; distribution unlimited.

11. SUPPLEMENTARY NOTES

12. SPONSORING MILITARY ACTIVITY

Naval Postgraduate School
Monterey, California 93940

13. ABSTRACT

A system for the determination of dissolved gases in seawater by gas chromatography was constructed and used to find the concentrations of methane and carbon monoxide in a variety of habitats around the Monterey Peninsula. Methane was shown to have a maximum of 2.8×10^{-4} ml/l at 50 meters at the open ocean station, with a surface value of 1.1×10^{-4} ml/l. The surface waters at the nearshore stations were almost three times this value. Methane was also shown to be an effective tracer for sewage effluent. The carbon monoxide maximum of 2.1×10^{-4} ml/l was found at 15 meters which correlated closely with primary productivity (Rowney 1973). The surface values of 0.81×10^{-4} ml/l was lower than the nearshore values. All stations sampled were found to be highly supersaturated with both gases. This indicates that in this area, the ocean is a major source of both methane and carbon monoxide.

KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
gas chromatography						
methane						
carbon monoxide						
dissolved gases						
gradient analysis						
gas analysis						
seawater analysis						
pollution						

10 JUN 75

23879

Thesis
W393
c.1

Welch

144171

Gradient analysis of
carbon monoxide and
methane in polluted and
other nearshore habitats.

10 JUN 75

23879

Thesis

W393

c.1


Welch

Gradient analysis of
carbon monoxide and
methane in polluted and
other nearshore habitats.

144171

thesW393

Gradient analysis of carbon monoxide and



3 2768 001 95201 3

DUDLEY KNOX LIBRARY